



Intermec

Product Profile



- Field-proven industrial strength
- Superior print quality
- Prints extremely small labels on demand
- Unparalleled PrecisionPrint™ Technology
- Versatile connectivity includes choice of Serial, Parallel, Twinax/Coax, EasyLAN™ Ethernet
- Free Intermec Printer Network Manager (IPNM) software
- Free LabelShop® label design and print software

EasyCoder® 3240 PRINTER

Printing small labels for electronic components, printed circuit boards, test tubes and vials can be challenging, particularly for rival label printers. However, with Intermec's EasyCoder 3240 printer, it's a snap. Two of Intermec's technologies, 400-dpi print resolution and Intermec's patented PrecisionPrint technology, provide perfect label-to-label image registration.

Intermec's exclusive PrecisionPrint technology ensures continuous image registration on the label within a tolerance of ± 0.030 inches (.762 mm). The EasyCoder 3240 printer excels even on the smallest labels, measuring only 0.1 inch in length, where problems with image registration show up immediately.

In addition to printing on small or oddly shaped labels, the 3240 is perfect for printing on a variety of substrates that are difficult to print on, such as Kapton or

ultra-smooth polyesters and synthetics. That's why so many organizations in electronics and health care have turned to Intermec for printers.

The optional internal EasyLAN Ethernet allows for network management without the complexity, space requirements, and vulnerability of external print servers.

Intermec's Printer Network Manager (IPNM), LabelShop® START design and print software, and InterDriver™ Windows printer driver are included, free of charge, with every printer.

Beyond the power and precision, the EasyCoder 3240 is the printer of choice when the application calls for printing complex images on extremely small labels or unique materials.

Intermec

Application

Direct Thermal and Thermal Transfer printer for self-adhesive label, ticket and tag applications.

Model

EasyCoder 3240

Physical Characteristics

Length: 43.8 cm (17.25 in)
Height: 27.7 cm (10.9 in)
Width: 21.1 cm (8.3 in)
Weight: 14.5 kg (32 lbs.)

Print Registration

- PrecisionPrint™ technology yields consistent image placement over an entire 6,000 inch roll of media
- Image accuracy is within .030 of an inch in batch or print and retract modes

Print Specifications

Maximum Width: 64 mm (2.5 in)
Maximum Length: Unlimited
Element: 0.062 mm (0.00246 in)
"X" Dimension: 0.06 to 1.27 mm (2.5 to 50 mil)

Print Speed

Selectable Print Speeds: 51 mm/s (2 ips) to 102 mm/s (4 ips)

Print Resolution

16 dots/mm (406 dots per inch)

Media Specifications

Style: Roll-feed, die-cut, continuous or fanfold labels, tags, or tickets
Type: Plain paper thermal transfer or thermal sensitive papers
Maximum Liner Width: 71 mm (2.8 in)
Minimum Liner Width: 19 mm (.5 in)
Maximum Media Length: 2.5 to 610 mm (0.1 to 24 in)
Thickness: .08 mm to .30 mm (.003 to .012 in)

Supply Roll Capacity: 152 m (6,000 in linear)
Core Size: 76 mm (3 in)

Ribbon Specifications

Type: Wax, wax/resin, resin
Standard Width: 30 mm (1.2 in) or 71 mm (2.8 in)
Length: 152 m (6,000 in linear)

Interface

Standard:

- RS-232 Serial

Optional:

- Centronics Parallel
- Internal IBM Twinax or Coax
- Internal EasyLAN™ Ethernet 10BaseT

EasyLAN Ethernet Supported Protocols: TCP/IP-suite (TCP, UDP, ICMP, IGMP, etc.), LPR/LPD, FTP, BOOTP, DHCP, HTTP, SNMP, SMTP. SNMP-MIB II supported (over UDP/IP), private enterprise MIB included

Software

Available printer command languages:

- IPL

Applications/Drivers (comes on Printer Companion CD) including:

- InterDriver™ Windows printer driver
- Intermec LabelShop® START label design and print package
- Intermec Printer Network Manager (IPNM) for administration of network connected printers
- PrintSet for printer configuration

Bar Code Symbologies

1-Dimensional: Code 2 of 5, Codabar, Code 11, Code 39, Code 93, Code 128, HIBC, Interleaved 2 of 5, Postnet, UPC/EAN, JIS-IFT
2-Dimensional: Code One, Code 16K, Code 49, DataMatrix, PDF417, QR Code, MaxiCode, MicroPDF

Character Sets

Code page 850, French, German, ISO 256 character, Italian, Kanji/Katakana (optional), Norwegian/Danish, Spanish, Swedish/Finnish, Swiss, UK, ASCII, USA ASCII

Fonts and Graphics

21 resident bitmapped fonts (includes OCR-A and OCR-B), 3 resident outline fonts, supports user-defined fonts and graphics.

Power Supply

Voltage range: 100, 115, 200, 230 VAC ± 10%
Frequency range: 50 to 60 Hz

Environment

Operating Temperature: 4° to 40° C (40° to 104° F)
Storage Temperature: -20° to 70° C (-4° to 158° F)
Humidity: 10 to 90% (non condensing)
Ventilation: Free air

Regulatory Approvals

Complies with FCC Part 15, Class A; CISPR 22 Class B; ICES-003 Class B; UL, CSA & TUV-GS agency approved; CE, NOM & C-TIC

Options

Centronics Parallel; Twinax and Coax; Internal EasyLAN™ Ethernet; Memory expansion to 512K NVRAM; Kanji/Katakana Fonts

上海公司 :

电 话 : 0 2 1 - 5 2 3 9 8 0 5 1 / 2 / 9

传 真 : 0 2 1 - 5 2 3 9 8 0 6 9

地 址 : 上海市中山北路 3 0 0 0 号 (曹杨路口) 长城大厦 1 0 0 8 室

香港公司 :

电 话 : (8 6) 1 3 9 0 6 2 0 3 3 3 6

传 真 : 0 5 1 2 - 6 5 2 4 0 6 2 2

地 址 : 香港中环荷李活道 3 2 号建业荣基中心 9 楼 9 0 1 B

无锡公司 :

电 话 : 0 5 1 0 - 8 5 2 1 9 9 3 0、8 5 2 2 6 3 2 0、8 5 2 2 7 5 2 0

传 真 : 0 5 1 0 - 8 5 2 2 7 5 2 0

地 址 : 无锡长江路 5 号东方银座大厦 5 - 2 号 3 0 6 室

苏州公司 :

电 话 : 0 5 1 2 - 6 5 2 4 0 6 6 1、6 5 2 4 5 8 0 7、6 5 2 4 1 1 9 3

传 真 : 0 5 1 2 - 6 5 2 4 0 6 2 2

地 址 : 苏州市干将东路 8 7 9 号瑞基大厦 6 层